

Phileas<sup>®</sup> 5

Fixed and mobile for very small volumes



Autonomous Airborne Surface Disinfection (ASD) device, with unique technique of dry fog using the piezoelectric technology.

Multi-nozzle and separable unit for more efficient disinfection of very small volumes: nozzles to be placed inside the space to be treated, the control box remains outside for easy and safe monitoring. Integrated and mobile, the best of both worlds!

### Technical characteristics

#### Volume treated: 50 up to 1000L

2 nozzles on cords, to be positioned on the wall of the surface to be treated

#### Device's flowrate: 420 mL/hr

Diffusion time: 1min45 for 1000L at 12 mL/m $^3$  for

example

#### Droplets size: 4-12 µm

Up to 20 consecutive cycles

Biocide tank: 250mL

Power: 20W

Total size (l x w x h): 212 x 295 x 243 mm

Separable unit size (I x w x h): 148 x 123 x 160 mm

Weight: 5.5kg (total), 1.5kg (separable unit)

Material compatible with O2SAFE7.4® and

Phileasafe®

Minimum maintenance, robust device

Works on mains power

Power supply: 100-240V, 50/60Hz, 1.8A

Indication: final disinfection after cleaning

# After-cleaning three-step disinfection



#### 1- Diffusion

#### Microdrop Phase

the biocide sprayed in nonwetting fog covers the entire surfaces

#### 2- Contact time

#### Steam Phase

- Small droplet size allows to shorten the evaporation time
- Biocide enters the microbial cells and kills it

#### 3- Aeration

Recovery after 20 air changes

Performance, Safety, Simplicity & Rapidity for the following applications:



Research laboratories



Pharmaceutical industries



Biotech industries



Glove boxes, incubators, isolator, RABS



## Phileas<sup>®</sup> 5

Fixed and mobile for very small volumes



### Performance

- 4-log<sub>10</sub>, 5-log<sub>10</sub>, 6-log<sub>10</sub> microorganism decrease depending on the goals
- of the Adaptation protocol according the requirements and disinfection level to achieve
- Homogenous & qualitative dry fog thanks to its unique nozzle technology

### Rapidity

- Last zone variables memorized for fast disinfection cycle launch
- Volume treatment in as fast as 1 minute 45 for 1 m³ at 12mL/m<sup>3</sup>
- Piezoelectric nozzle nebulisation technology, perfect for very small spaces: dry fog technology and optimised contact time

### Security

- Maintenance kit supply, for reliable disinfection cycle each time
- Remote monitoring, no contact with the biocide thanks to its separable unit
- Easy and automatic programming system, reducing the risk of errors
- Phileasafe®: Compatible O2SAFE7.4® with and ≤7.4% H<sub>2</sub>O<sub>2</sub> concentration, safe for users and non corrosive for equipment
- O2SAFE7.4® is 100% biodegradable, additive free and residue free

### Control and data analysis

- Easy programming and total autonomy with two criteria: volume and concentration
- Automatic calculation of the diffusion time
- Variables and treatment area memorisation functionality
- Touch screen and fast control set up

### Why Devea?

- Biodecontamination expertise with the most demanding sectors
- Devea Services:
  - Protocol support & personalized advice
  - Maintenance kit & step by step guided maintenance manual
  - Biological and chemical indicators provision
  - After-sale service & equipment repair diagnostic under 48hrs
- A range of products adapted for all volumes
- Design, manufacture and maintenance in France (Nantes)







puminski@devea-environnement.com

